



## Fibre cassette

### LinkIT MTP Cassette 24 x LC OM3

2 x MTP 12 core ports. USConec

Product number: MTP2-LCX24OM3

## Product Description

The cassette has a rational structure and high capacity. It can be used in telecommunication networks, CATA networks, FTTH, LAN, WAN, etc. The cassette uses an angled polished LC connector with low insertion loss.

Inside the cassette is a breakout cable assembly, which uses a Corning fiber in a ribbon configuration for 24 LC connections as the result is connected with 24 LC patch cables on the front of the cassette, and an MTP / MPO 24 UPC connector in the back of the cassette. The cassette can be installed in either vertically or a horizontal MPO cassette holder.

## Main Specifications

<b>Brand</b>	LinkIT
<b>Color</b>	Black
<b>Measurements (WxHxD)</b>	121,2 x 77 x 130,87
<b>Material</b>	Steel
<b>Fibreclass</b>	Multimode OM3 50/135um
<b>Front Connector Color</b>	LC/SC Multimode OM3/OM4: Aqua
<b>Rear Connector Color</b>	MTP Multimode OM3/OM4: Aqua
<b>Front Adapter Color</b>	LC/SC Multimode OM3/OM4: Aqua
<b>Number of outputs</b>	24
<b>Type of inputs</b>	LC adapter

## Extended Specifications

<b>Operating Temperature</b>	-10°C-60°C
------------------------------	------------



<b>Input</b>	2 x MTP adapter
<b>Cable</b>	2 x 12C MTP Male-LC 0.9mm 25cm
<b>Front Connector</b>	Multimode LC/SC Duplex with UPC Polish
<b>Insertion Loss Front Connector</b>	Multimode: UPC $\leq$ 0.25dB
<b>Return Loss Front Connector</b>	Multimode: UPC $\geq$ 30dB
<b>Rear Connector</b>	Multimode US Conec MTP Male Ferrules and UPC
<b>Insertion Loss Rear Connector</b>	Multimode: Standard UPC $\leq$ 0.6dB Elite UPC $\leq$ 0.35dB
<b>Return Loss Rear Connector</b>	Multimode: $\geq$ 20dB
<b>Front Adapter</b>	12pcs LC Duplex Adapter without flange
<b>Rear Adapter</b>	2 pcs MTP Adapter Standard
<b>Certifications</b>	CE, RoHS

## Single packaging

<b>Unit</b>	BOX
<b>Quantity</b>	1
<b>Height (cm)</b>	7,7
<b>Width (cm)</b>	12,1
<b>Depth (cm)</b>	13
<b>Weight (kg)</b>	0
<b>Gross Weight (kg)</b>	0

