



## DisplayPort

**(Copy) LinkIT DisplayPort cable 1.4 M-M  
0,5 m**

4K x 2K@120Hz 30 AWG black version 1.4

Product number: CDP-DP14-0005

## Product Description

DisplayPort M-M 1.4 cable. The display port cable is used to send audio and video from a source with Displayport plug to display with Displayport plug. 32.4Gbps bandwidth. Leads of pure copper. Maximum resolution: 4Kx2K @ 120Hz (8K).

## Main Specifications

<b>Brand</b>	LinkIT
<b>Color</b>	Black
<b>Length (m)</b>	0,5
<b>Connector type 1</b>	DP Male 20 pin w/interlock
<b>Connector type 2</b>	DP Male 20 pin w/interlock
<b>Conductor material</b>	Copper
<b>Cable shielding</b>	Triple shielding
<b>DisplayPort version</b>	1.4
<b>Max Resolution</b>	7680x4320@60hz
<b>Bandwidth</b>	32.4Gbps

## Extended Specifications

<b>Active</b>	X
<b>AWG wire size</b>	30



<b>Transmission speed</b>	32.4Gbps
<b>Jacket material</b>	PVC
<b>Anti-kink sleeve</b>	Assembled
<b>Inner Cast</b>	PE
<b>Halogenfree</b>	X
<b>EAN</b>	7072262005263
<b>Certifications</b>	REACH, RoHS

## **Single** packaging

<b>GTIN f-pak</b>	
<b>Unit</b>	PCE
<b>Height (cm)</b>	12,5
<b>Width (cm)</b>	12,5
<b>Depth (cm)</b>	2
<b>Weight (kg)</b>	0,042
<b>Gross Weight (kg)</b>	0,047



## Dimensional Sketches

RevNo	Revision note	Date	Signature	Checked

P/N	L/(mm)	T/(mm)
123492 CDP-DP14-0005	500	30
123493 CDP-DP14-0010	1000	30
123494 CDP-DP14-0015	1500	30
123495 CDP-DP14-0020	2000	30

**NOTES:**

1. OPEN/SHORT/INTERMITTENCE: 100%
2. INSULATION RESISTANCE:300V 0.01S 10MΩ Min
3. CONDUCTIVE RESISTANCE:3Ω Max
4. HI-POT:150V AC 0.01S 1mA
5. RESOLUTION TEST:8K\*4K@60HZ
6. RoHS & REACH COMPLIANT

**PIN OUT**

<p>P1</p>	<p>P2</p>	<p>P1</p>	<p>P2</p>
-----------	-----------	-----------	-----------

SHELL — DRAIN — SHELL

NO.	MATERIAL	DESCRIPTION	QTY.	UNIT
⑧	DUST CAP	DP MALE LDPE	2	PCS
⑦	LABEL	CONTENT:DP1.4V 8Kx4K@60HZ	1	PCS
⑥	COPPER FOIL	DOUBLE SIDED CONDUCTIVE FOIL	2	PCS
⑤	MOLDED	4SP BLACK PVC		G
④	MOLDED	LDPE		G
③	PLASTIC HOOD	DP MALE BLACK PLASTIC HOOD	2	SET
②	CONNECTOR	DP MALE, GOLD PLATED PIN, BLACK INSULATION, GOLD PLATED SHELL	2	PCS
①	CABLE	[(7/0.10TC)*1P+D(7/0.10TC)+FAM]*5C+(7/0.10TC)*4C+AL+D(7/0.10BC)+B(16/7/0.12AL-MG) BLACK PVC JACKET OD:6.0±0.2MM MARKING:DisplayPort Cable E***** 8K 4K STYLE 20276 80°C 30V VW-1	L	M

Itemref	Quantity	Title/Name, designation, material, dimension etc	Article NO./Reference
Designed by FLY	Checked by HELEN	Approved by - date 2023.10.18	File name Date 2023.10.18 Scale FREE
ANGLE:			DP1.4 M-M BLACK PVC
UNIT:MM			Edition 1 Sheet 1/1

